


## ROsave.Z™s

Depth Cartridge Filter for Reverse Osmosis Pretreatment  
Applications with Z.Plex™ Filter Technology

***ROsave.Zs is manufactured using revolutionary Z.Plex Filter Technology, and offers unmatched performance in a depth filter.***

**Features and Benefits**

ROsave.Zs is manufactured using patent pending Z.Plex filter technology and is engineered for reverse osmosis pretreatment and other pure water applications. ROsave.Zs' proprietary filter matrix provides unmatched performance in these applications.

- > Up to twice the life of conventional depth filters
- > Up to 50% lower pressure drop
- > Up to 100% greater dirt holding capacity
- > Superior SDI reduction
- > Melt-bonded exterior ensures no media migration
- > Provides lower total cost of filtration operations
- > NSF 42, FDA approved

**Applications**

Reverse osmosis pretreatment in industries including:

- > Bottled water
- > Beverage
- > Electronics

**Materials of Construction**

- > 100% polypropylene construction

**Dimensions**

Nominal O.D.	Nominal I.D.
2.5"	1.0"

**Micron Ratings, Lengths and End Adapters**


- > Micron ratings: 1 and 5 micron
- > Standard lengths fit most housings - custom lengths are also available
- > Wide range of end adapters including self-sealing spring, 222 and 226 O-rings, and extended cores.

## Additional Information

ROsave.Zs cartridge filters are made from thermally-bonded fibers of polypropylene. GE certifies that it uses no resin binders, lubricants, antistatic or release agents or other additives in the manufacture of these cartridges, and that the resin used for manufacturing the filter media meets the food contact requirements of U.S. FDA 21CFR regulations. When required, specify only FDA compliant sealing materials and end-adapters.

GE filter cartridges are designed and manufactured for resistance to a wide range of chemical solutions. Conditions will vary with each application and users should carefully verify chemical compatibility. Please contact your GE representative for more information.

## ROsave.Zs 1 and 5 micron versus Conventional 5 micron Flow Performance in Clean Water\*



\* Typical Data based 10" length filter

## Ordering Information

If you are ordering ROsave.Zs filters with standard ends (with no adapter on either end), select one designation from each of the first three columns. Your Product Order Number will look like this: **RO.Zs 05-40**. If you are ordering ROsave.Zs with end adapters, select designations from all applicable columns. Your Product Order Number will look like this: **RO.Zs 05-40 XK**.

Type	Micron Rating mm	Cartridge Length Inches (cm)	End 1 Adapter	End 2 Adapter	Material
RO.Zs I.D. = 1.0 O.D. = 2.5	01 = 1	9 3/4 (24.8)	L = Extended Core	K = Self seal spring	<b>O-Rings</b>
	05 = 5	9 7/8 (25.1)	E = 222 O-Ring	H = Fin	S = Silicone
		10 (25.4)	F = 226 O-Ring	S = Solid End	E = EPDM
		19 1/2 (49.5)	X = Standard		V = Viton*
		20 (50.8)	ROsave.Zs plain end (no gasket)	X = Standard ROsave.Zs plain end (no gasket)	B = Buna
		29 1/4 (74.3)			
		30 (76.2)			
		40 (101.6)			

\* Viton is a trademark of DuPont Dow Elastomers.

