

SeaPRO* Series 60 Hz

Seawater Desalination Machines 45,000 ppm NaCl
20-60 gpm (4.5-13.6 m³/hr)



Basic Features (BAS)

- GE Fanuc Quick Panel 6-inch, 6-inch color display, Primarily text operating screens, Touchscreen controls
- GE Fanuc Micro VersaMax, Communication: RS232/DH485, Analog output: 6 points
- 4-20 mA instruments displayed on instrument center
- Variable frequency drive (VFD) for high pressure pump
- Stand alone master control enclosure, skid mounted local control enclosure with terminal strips

Premium Features (PRE)

- GE Fanuc QuickPanel 12-inch, 12-inch color display, Text and pictorial operating screens, Touchscreen controls
- GE Fanuc VersaMax Communication: RS232 /DH485/Ethernet, Analog output: 4 points
- 4-20 mA instruments on PanelView
- Primary and final pressure transmitters
- Variable frequency drive (VFD) for high pressure pump
- Automated valves and control for full permeate flush upon shut down
- Stand alone master control enclosure, skid mounted local control enclosure w/remote I/O

Instrumentation

Flow Meters.....Permeate, concentrate
Conductivity.....Permeate
pH Feed
Pressure..... Pre-filter, post-filter, primary, final,
permeate, concentrate,pump discharge
(PRE Feature = Primary, Final transmitter)

a product of

ecomaginationSM



Instrumentation (continued)

Pressure Switch.....Feed, permeate, concentrate
Instrument center Thornton 770 MAX

Options Available

- Allen Bradley control system
- Multi-Media filters
- Clean-in-Place (CIP) units
- Chemical feed systems

Documentation Included

- Operation and maintenance manual
- Control narrative
- Drawings: piping and instrumentation, electrical and general dimensional

Operating Parameters

Recovery..... 35%
Design temp. 77°F (25°C)
Design Feed TDS..... 45,000 ppm NaCl
Operating range 35 to 85°F (1.6 to 29.4°C)
Minimal inlet pressure30 psi (2 Bar)

Materials of Construction

High-pressure piping..... Sch. 10, Duplex 2205
Stainless Steel
Low-pressure piping.....Sch. 80, PVC
Frame.....Painted carbon steel
Local Enclosure FRP, NEMA 4X

Find a contact near you by visiting www.gewater.com and clicking on "Contact Us".

* Trademark of General Electric Company; may be registered in one or more countries.

©2013, General Electric Company. All rights reserved.

Materials of Construction (continued)

Main Enclosure Painted carbon steel, NEMA 4
 VFD Enclosure Painted carbon steel, NEMA 4
 Clamps/fittings Zinc-plated

Cartridge Filtration

Housing material GRP (glass reinforced plastic)
 Cartridge filter 5-micron nominal, ROsave.Zs

Membrane Elements and Housings

Style Spiral-wound elements
 Membrane type AD-400
 Element Area 400 ft²
 Average membrane flux 8-10 GFD
 Housing material FRP, 80 Bar (1200 psi)
 Housing closure type ... Ring and plate style closure



SeaPRO Models

MODEL	SeaPRO-8	SeaPRO-16	SeaPRO-28
Permeate rate:	28.8k gpd 20 gpm (4.5 m ³ /hr)	57.6k gpd 40 gpm (9.0 m ³ /hr)	86.4k gpd 60 gpm (13.6 m ³ /hr)
Concentrate Rate:	37 gpm (8.4 m ³ /hr)	74 gpm (16.8 m ³ /hr)	111 gpm (25.2 m ³ /hr)
Feed Rate:	57 gpm (12.9 m ³ /hr)	114 gpm (25.8 m ³ /hr)	171 gpm (38.8 m ³ /hr)
Pumps and Motors			
Model:	MSS 1537	MSS 2030	MSS 3030
Manufacturer:	GE Osmonics/FEDCO [®]	GE Osmonics/FEDCO [®]	GE Osmonics/FEDCO [®]
Quantity:	1	1	1
Motor HP and type:	40Hp (29.9 kW) TEFC	75 Hp (55.9 kW) TEFC	100 Hp (74.6 kW) TEFC
Design Flow Rate:	60 gpm (13.6 m ³ /hr)	115 gpm (26.1 m ³ /hr)	170 gpm (38.6 m ³ /hr)
Design boost pressure:	690 psig (47.6 Bar)	660 psig (45.5 Bar)	620 psig (42.7 Bar)
Energy Recovery Booster			
Model:	HPB 20	HPB 30	HPB 40
Manufacturer:	GE Osmonics/FEDCO [®]	GE Osmonics/FEDCO [®]	GE Osmonics/FEDCO [®]
Quantity:	1	1	1
Design boost pressure:	315 psig (21.7 Bar)	340 psig (23.4 Bar)	380 psig (26.2 Bar)
Membrane Elements and Housings			
Membranes quantity:	8	16	24
Memb. housing style:	4 element long, 4 port	4 element long, 4 port	4 element long, 4 port
Banking Arrangement:	2, parallel	4, parallel	6, parallel
Cartridge Filtration			
Cartridge Filter:	RO.Zs05-40XK	RO.Zs05-40XK	RO.Zs05-40XK
Filter Length:	40" (102 cm)	40" (102 cm)	40" (102 cm)
Filter Quantity:	6 per change out	10 per change out	22 per change out
Installation and Utility Requirements			
Inlet:	2.0" flange	3.0" flange	3.0" flange
Permeate:	1.0" flange	1.5" flange	2.0" flange
Concentrate:	1.5" flange	2.0" flange	3.0" flange
Inlet Water Pressure:	30 psig, minimum	30 psig, minimum	30 psig, minimum
Air Pressure:	100 psig, oil-free	100 psig, oil-free	100 psig, oil-free
Drain to be Sized for:	57 gpm (12.9 m ³ /hr)	114 gpm (25.8 m ³ /hr)	171 gpm (38.8 m ³ /hr)
Power:	230/460 VAC, 3-phase, 60Hz	230/460 VAC, 3-phase, 60Hz	230/460 VAC, 3-phase, 60Hz
Control Circuit:	120 VAC, 1-phase, 60Hz	120 VAC, 1-phase, 60Hz	120 VAC, 1-phase, 60Hz
SeaPRO Skid			
Height:	88" (224 cm)	88" (193 cm)	88" (224 cm)
Width:	52" (132 cm)	52" (117 cm)	52" (132 cm)
Depth:	199" (506 cm)	199" (506 cm)	199" (506 cm)
Weight Estimate for Shipping Purposes:	3400 lb (1542 kg)	4000 lb (1814 kg)	4500 lb (2041 kg)